





6" CS-3020 Sliding Coldshoe

Pipe size	L=12" Vertical Load(lbs)	L=18" Vertical Load(lbs)	Insulation Thickness											
			1"			1-1/2"			2"			2-1/2"		
			W	O.D.	H	W	O.D.	H	W	O.D.	H	W	O.D.	H
1/2"	162	232	3"	3-1/8"	4"	4"	4-1/4"	4"	4"	5-1/4"	4"	4"	6-7/8"	4"
3/4"	203	290	3"	3-1/8"	4"	4"	4-1/4"	4"	4"	5-1/4"	4"	4"	6-7/8"	4"
1"	254	363	4"	3-3/4"	4"	4"	4-3/4"	4"	4"	5-13/16"	4"	4"	6-7/8"	4"
1-1/4"	321	459	4"	3-3/4"	4"	5"	5-1/4"	4"	4"	5-13/16"	4"	4"	6-7/8"	4"
1-1/2"	368	525	4"	4-1/4"	4"	4"	5-1/4"	4"	4"	6-7/8"	4"	4"	7-7/8"	4"
2"	459	656	4"	5"	4"	4"	6-1/16"	4"	4"	7-1/4"	4"	4"	8-1/8"	4"
2-1/2"	556	794	4"	5-1/2"	4"	4"	7-1/8"	4"	4"	8-1/8"	4"	4"	9-1/8"	4"
3"	677	967	4"	6-1/16"	4"	4"	7-1/8"	4"	4"	8-1/8"	4"	4"	9-1/8"	4"
3-1/2"	774	1105	4"	7-1/8"	4"	4"	8-1/8"	4"	4"	9-1/8"	4"	4"	10-1/8"	4"
4"	870	1243	4"	7-1/8"	4"	4"	8-1/8"	4"	4"	9-1/8"	4"	4"	10-1/8"	4"
5"	1076	1537	4"	8-1/8"	4"	4"	9-1/8"	4"	4"	10-1/8"	4"	4"	11-1/4"	4"
6"	1281	1831	4"	9-15/16"	4"	4"	10-3/8"	4"	4"	11-1/2"	4"	4"	12-1/2"	4"

Pipe size	L=12" Vertical Load(lbs)	L=18" Vertical Load(lbs)	Insulation Thickness								
			3"			3-1/2"			4"		
			W	O.D.	H	W	O.D.	H	W	O.D.	H
1/2"	162	232	4"	7-7/8"	6"	4"	8-7/8"	6"	4"	9-7/8"	6"
3/4"	203	290	4"	7-7/8"	6"	4"	8-7/8"	6"	4"	9-7/8"	6"
1"	254	363	4"	7-7/8"	6"	4"	8-7/8"	6"	4"	9-7/8"	6"
1-1/4"	321	459	4"	7-7/8"	6"	4"	8-7/8"	6"	4"	9-7/8"	6"
1-1/2"	368	525	4"	8-7/8"	6"	4"	9-7/8"	6"	4"	11"	6"
2"	459	656	4"	9-1/8"	6"	4"	10-1/8"	6"	4"	11-1/4"	6"
2-1/2"	556	794	4"	10-1/8"	6"	4"	11-1/4"	6"	4"	12-1/4"	6"
3"	677	967	4"	10-1/8"	6"	4"	11-1/4"	6"	4"	12-1/4"	6"
3-1/2"	774	1105	4"	11-1/4"	6"	4"	12-1/4"	6"	4"	13-1/4"	6"
4"	870	1243	4"	11-1/4"	6"	4"	12-1/4"	6"	4"	13-1/4"	6"
5"	1076	1537	4"	12-1/4"	6"	4"	13-1/4"	6"	4"	14-1/2"	6"
6"	1281	1831	4"	13-1/2"	6"	4"	14-3/4"	6"	4"	15-3/4"	6"